

# elap



## CM78N C01/C02 **MICROPROCESSOR COUNTER/VISUALISER**

The new counter **CM78N** includes the basic features of CM78 while it enhances its performance; indeed in the same size as CM78 it encloses a high number of functions. **CM78N C01** operates as **2-preset counter**, as **partial/total counter** and as **cycle counter with cycle preselection**, while **CM78N C02** is a **position visualiser**, a **visualiser with two settable thresholds** and an **absolute/relative visualiser with two settable thresholds**. Several parameters can be set by the user simply and directly. The counter **CM78N** can replace a CM78 unit pin-to-pin; its functions currently replace the ones covered by programs S001-S002-S006-S007-S012-S017-S018-S020-S026-S032 of CM78 H1<sup>(1)</sup>.

### OPERATING MODES

▪ <b>CM78N C01</b>	▪ <b>CM78N C02</b>
<ul style="list-style-type: none"><li>▪ <b>Up/down counter with settable cycle</b></li><li>▪ <b>Partial/total counter with settable cycle</b></li> <li>▪ <b>Cycle counter with settable cycle</b></li></ul>	<ul style="list-style-type: none"><li>▪ <b>Position visualiser</b></li><li>▪ <b>Position visualiser with two settable thresholds</b></li><li>▪ <b>Absolute/relative visualiser with two settable thresholds</b></li></ul>

### GENERAL SPECIFICATIONS

- 6 displayed digits
- mono/bidirectional input
- count frequency (primary wave) 25 KHz
- 2 relay outputs 250V 3A
- 2 presets
- NPN or push-pull encoder inputs
- supply voltage 115 or 230 or 24Vac, 50/60Hz or 12 or 24 Vdc (to be defined in the order)
- microprocessor with re-writable memory
- operating modes can be freely set by the user:
  - decimal point position
  - correcting factor from 0.01 to 9.99999
  - multiplication of the input pulses by 1 or by 4
  - 12÷24 Vdc externa functional inputs NPN or PNP, selectable by software
  - single or repeat cycle, up or down counter (for type C01 only)
  - solid state or time outputs
  - partial/total counter (type C01) or absolute/relative visualiser (type C02)
  - cycle counter (type C01 only)
- Dimensions: mm 96x48, dept mm 105, panel cut off mm 92x45

**POPHOF Antriebstechnik**  
Schützenstr. 14a, D-77933 Lahr,

Tel. 07821-983 913, Fax 07821-983 914,  
info@pophof.de www.pophof.de

s.p.a. Via Vittorio Veneto, 4 - I-20094 CORSICO (MI) - Tel. ++39.02.4519561  
Fax ++39.02.45103406 E-mail: elapspa@tin.it URL: www.elap.it